

NEW

1/8 DIN SERIAL REMOTE DISPLAY & CONTROLLER

For DCS, SCADA or Stand Alone

**MODEL
SRD**

FEATURES:

- 4 1/2 LED or LCD 0.6" Digits
- 3 1/2 LED 0.8" Digits
- 5, 10-32VDC or 90-265VAC Power
- Inputs For: ASCII
- RS232, 485, or USB
- Watchdog Timer/Checksum
- Relay (4) Output
- Analog (1) Output
- Open Collector (4) Output
- Lifetime Warranted

4 1/2 LCD (Option 4)



4 1/2 LED (Option 0)



4 LED (Option 6)



SPECIFICATIONS (Industrial)

(at 25°C & 5VDC)

- Digits: 4 1/2 ea. 0.6" High with 5 D.P. or 3 1/2 ea. 0.8"
- Power Consumption: 1 Watt
- Isolated Power Input: 500VDC
- Baud Rate: 1200 to 19,200 (9600 Default)
- Characters: ASCII Codes 0-9 & Modified Alpha & DP
- Hardware Handshake: None Required
- Operating Temp: 0-60°C, NEMA 4
- Storage Temp: Between -20 and + 80°C
- Humidity: 5-95% RH, Non-Condensing
- Calculated MTBF: >100,000 Hours (12+ Years)
- Warranty: Lifetime (LTD)
- Addresses: 6 Digits via Serial (001 Default)

Note 1: Above specifications are for Industrial Grade. Contact OTEK for other grades.

DESCRIPTION:

With over 30 years in the Digital Panel Meter field, we had to bring you the best that technology would allow. The SRD is a combination of that expertise and newest technology in an industry standard 1/8 DIN package. The modular construction allows **OTEK** to customize your needs without expensive N.R.E., set-ups or minimum orders.

Remote Display:

You can use USB, RS232 or 485 to address the SRD. It accepts industry standard ASCII characters and displays all numerals and standard seven segment alpha characters, you can address up to 6 digits (001 reserved for default), the setting is "8N1" and accepts baud rates from 1200-19.2KB.

Remote Controller:

If you want to control your process via the SRD, you can do it with either relays (4) with normally open contacts (N.C. on request) rated at 1 Amp @ 30VDC/120VAC, or 4 open collector transistors (O.C.T) rated at 30mA @ 30VDC (common emitter).

If you want analog output, select this option for standard 4-20mA. Contact OTEK for your custom requirements.

Displays: You can order the large 0.8" 3 1/2 LED or the 0.6" 4 1/2

LED or LCD. The LCD is Reflective or Backlit.

APPLICATIONS:

- D.C.S./SCADA
- Shipboard/Avionics
- Nuclear & Mil-Spec
- Offshore Exploration



**If You Don't See It,
Ask For It!**

OTHER RELATED MODELS:

- HI-QREM: 5 Digit Serial Remote Display
- HI-Q111: Miniature Case, 4 Digit Remote Display
- HI-Q112: 1/8 DIN, 4 Digit .8" Remote Display
- BCDPM: BCD Input Remote Display

520-748-7900

FAX: 520-790-2808
E-MAIL: sales@otekcorp.com
http://www.otekcorp.com

OTEK™
CORP.
SINCE 1974

4016 E. TENNESSEE ST.
TUCSON, AZ. 85714 U.S.A.



SRD SERIES ORDERING INFORMATION 10-26-11

Model: SRD -		1	2	3	4	5	6
GRADE (1)							
I	Industrial					
M	Mil-Spec					
N	Nuclear (Contact Otek)					
9	Custom (Specify)					
SERIAL I/O (2)							
1	RS232					
2	RS485					
3	USB					
9	Custom (Specify)					
POWER INPUT							
1	Non - Isolated 5VDC					
2	Isolated 5VDC					
3	Isolated 7-32VDC					
4	Isolated 90-265VAC					
5	Isolated 9-36VDC					
6	Isolated 48VDC					
7	Non-Isolated 7-32VDC					
9	Custom (Specify)					
DISPLAY TYPE							
0	4 1/2 Digits 0.6" Red LED					
1	4 1/2 Digits 0.5" LCD					
2	3 1/2 Digits 0.8" Red LED					
3	4 1/2 Digits 0.5" Red Backlit LCD					
4	4 1/2 Digits 0.5" Green Backlit LCD					
6	4 digits 0.8" Red LED					
9	Custom (Specify)					
CASE							
0	Plastic					
1	Metal					
2	Plastic/Nema 4X					
3	Metal/Nema 4X					
9	Custom (Specify)					
CONTROL & POWER OUT							
0	None					
1	Relays (4)					
2	O.C.T. (4)					
3	Isol. 4-20mA					
4	Isol. 30VDC For XMTR					
5	Relays & Isol. 4-20mA					
6	O.C.T. & Isol. 4-20mA					
7	Relays & Isol. 30VDC For XMTR					
8	O.C.T. & Isol. 30 VDC for XMTR					
9	Custom (Specify)					
A	Non-Isol. 28 VDC For XMTR					
B	Non-Isol. 4-20 mA Out					

NOTES:

- Otek will build to certain nuclear or MIL-standards but testing and confirmation of compliance, if required, will need to be done by a third party and at customer's expense. "M" & "N" grades must have metal case (Digit 5, Option 1).
- Serial I/O is **NOT** isolated from digital ground. Must have serial I/O to implement processor's functions (if req'd).

SRD MECHANICAL

